

6" WRANGLER

6" Wrangler
with 4"
Submersible
Motor
Bracket.



Wrangler 6" submersible pumps are designed for the high-capacity requirements of agricultural, commercial, industrial and municipal applications. Wrangler's quality construction assures years of reliable operation in the toughest performance environment.

- 6" High Capacity Submersible Pump End
- 3 through 25 HP
- 60, 90 and 140 GPM
- Cast Iron Motor Brackets Available for 4" or 6" Motors
- 3" NPT Discharge
- Stainless Steel

60 GPM WRANGLER PUMP SELECTION TABLE

C at No.	Motor HP	PSI	Depth to Water																	
			25	50	75	100	125	150	175	200	250	300	350	400	450	500	600	700	800	
64P360	3	0			85	73	57	38												
	3	20		76	62	42														
	3	40	63	45																
64P560 66P560	5	0					85	77	70	61	38									
	5	20					72	62	53	40										
	5	40				66	54													
	5	60	73	66	55	45														
64P760 66P760	7-1/2	0						85	81	85	75	65	54	38						
	7-1/2	20						77	72	68	66	55	39							
	7-1/2	40					83	77	72	68	66	55								
	7-1/2	60			83	78	74	68	63	58	54	43								
66P1060	7-1/2	80	83	79	74	69	63	57	52	40										
	7-1/2	100	74	69	64	59	53	46	35											
	10	0									82	74	66	58	50					
	10	20								84	75	68	60	51	40					
	10	40								83	75	68	60	51						
66P1560	10	60					84	80	77	69	63	53	43							
	10	80			83	80	76	73	70	63	54	43								
	10	100		83	81	78	74	71	67	63	54	43								
	15	0														80	76	66	54	37
	15	20													81	77	72	67	61	48
66P1560	15	40												81	77	72	67	62	55	39
	15	60												81	77	72	67	62	49	24
	15	80									81	77	73	68	62	56	40			
	15	100								82	78	73	68	63	57	50	27			